## **SAFETY DATA SHEET**



### 1. Identification

**Product identifier BLACKSNAKE-WP #88002** 

Other means of identification None

Recommended use Not available. **Recommended restrictions** None known.

Manufacturer/Importer/Supplier/Distributor information

Garon Products Inc **Company Name** 

PO Box 1924 **Address** 

Wall, NJ 07719

**USA** 

After hours telephone

1-800-631-5380

number

Normal work hours

8AM - 5PM EST

telephone number Website

www.garonproducts.com

customercare@garonproducts.com E-mail

**Emergency 24-hour** 

CHEMTREC: North America 1-800-424-9300 International 1-800-527-3887

telephone number

**Information on operation** 8:00 a.m. to 5:00 p.m.

hours

# 2. Hazard(s) identification

**Physical hazards** Not classified.

**Health hazards** Serious eye damage/eye irritation Category 2

Sensitization, skin

**Environmental hazards** Not classified. **OSHA** defined hazards Not classified.

**Label elements** 



Signal word

**Hazard statement** May cause an allergic skin reaction. Causes serious eye irritation.

**Precautionary statement** 

**Prevention** Wear eye protection/face protection. Avoid breathing dust/fume/gas/mist/spray. Contaminated

work clothing must not be allowed out of the workplace. Observe good industrial hygiene

practices. Wash thoroughly after handling.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present Response

and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. Wash contaminated clothing before reuse. Specific treatment see Section 4 of this SDS. IF ON SKIN: Wash with plenty of soap and water. If skin irritation or rash occurs: Get medical advice/attention.

Category 1

Store away from incompatible materials. **Storage** 

Disposal Dispose of waste and residues in accordance with local authority requirements.

Hazard(s) not otherwise

classified (HNOC)

None known.

Supplemental information Not applicable.

# 3. Composition/information on ingredients

**Mixtures** 

Material name: BLACKSNAKE-WP™ SDS US Version #: 01 Issue date: 12-08-2021 1/7

% **Chemical name Common name and synonyms CAS** number **ASPHALT** 8052-42-4 35 - 45 Other components below reportable levels 60.62

### 4. First-aid measures

**Inhalation** If breathing is difficult, remove to fresh air and keep at rest in a position comfortable for breathing.

Call a physician if symptoms develop or persist.

Skin contact If clothing sticks to the skin, do not remove. Lotion or hand cream may aid in the removal of

asphalt. Wash contact areas with soap and water. If needed, seek medical attention.

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if Eye contact

> present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists. Rinse mouth. DO NOT induce vomiting. Get medical attention immediately. If ingestion of a large

amount does occur, call a poison control center immediately.

Direct contact with eyes may cause temporary irritation.

Most important

**Ingestion** 

symptoms/effects, acute and delayed

**Indication of immediate** medical attention and special treatment needed

Treat symptomatically.

General information Ensure that medical personnel are aware of the material(s) involved, and take precautions to

protect themselves.

# 5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing

media

Specific hazards arising from

the chemical

Foam. Dry chemical powder. Carbon dioxide (CO2).

Water. Do not use water jet as an extinguisher, as this will spread the fire.

During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for

firefighters

Fire fighting equipment/instructions Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA. Structural firefighters protective clothing will only provide limited protection.

ALWAYS stay away from tanks engulfed in flame. Fight fire from maximum distance or use unmanned hose holders or monitor nozzles. Move containers from fire area if you can do so without risk. In the event of fire, cool tanks with water spray.

**Specific methods** In the event of fire and/or explosion do not breathe fumes. In the event of fire, cool tanks with

water spray.

**General fire hazards** No unusual fire or explosion hazards noted.

### 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up This product is miscible in water.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Prevent entry into waterways, sewer, basements or confined areas.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. Absorb or cover with dry earth, sand or other non-combustible material and transfer to containers. Ventilate area and avoid breathing vapors or mist. For large spills, dike far ahead of liquid spill for later disposal. Do not release into sewers or waterways.

**Environmental precautions** 

Avoid discharge into drains, water courses or onto the ground.

## 7. Handling and storage

Precautions for safe handling Avoid prolonged exposure. Use only in well-ventilated areas. Hydrogen sulfide, a very highly toxic

gas, may be present with this material. Keep face clear of tank and/or tank car openings. Good personal hygiene is necessary. Wash hands and contaminated areas with water and soap before

leaving the work site.

Conditions for safe storage,

including any incompatibilities Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in

original tightly closed container. Store in a well-ventilated place.

## 8. Exposure controls/personal protection

### Occupational exposure limits

<b>US. ACGIH</b>	Threshold	<b>Limit Values</b>
------------------	-----------	---------------------

Components	Туре	Value	Form	
ASPHALT (CAS 8052-42-4)	TWA	0.5 mg/m3	Inhalable fume.	
US. NIOSH: Pocket Guide to Chemical Hazards				
Components	Туре	Value	Form	

ASPHALT (CAS 8052-42-4)

No biological exposure limits noted for the ingredient(s).

Appropriate engineering controls

**Biological limit values** 

Provide adequate ventilation, including appropriate local extraction, to ensure that the defined

5 mg/m3

Fume.

occupational exposure limit is not exceeded.

Ceiling

Individual protection measures, such as personal protective equipment

Chemical goggles and face shield are recommended. Wear safety glasses with side shields (or **Eye/face protection** 

goggles).

**Skin protection** 

**Hand protection** Chemical resistant gloves are recommended. If contact with forearms is likely wear gauntlet style

gloves.

Other Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged

vapor contact. Plastic or rubber gloves, apron and boots.

Respiratory protection When workers are facing concentrations above the exposure limit they must use appropriate

certified respirators.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

**General hygiene** considerations

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to

remove contaminants.

### 9. Physical and chemical properties

**Appearance** Heavy-consistency emulsion.

Liquid. Physical state

**Form** Liquid. Viscous

Color Black

Odor Mild Petroleum Odor

**Odor threshold** Not available. 11 - 12 рH Melting point/freezing point 32 °F (0 °C) Initial boiling point and 212 °F (100 °C)

boiling range

> 212.0 °F (> 100.0 °C) Cleveland Open Cup

Not available.

**Evaporation rate** Not available. Flammability (solid, gas) Not available. Upper/lower flammability or explosive limits Flammability limit - lower Not available.

(%)

Flash point

Not available. Flammability limit upper (%) Explosive limit - lower Not available.

(%)

**Explosive limit - upper** 

(%)

Not available. Vapor pressure Vapor density Not available. Relative density 0.95 - 1.05 g/cm3 Relative density temperature 39.2 °F (4 °C)

Solubility(ies)

Solubility (water) Slightly **Partition coefficient** Not available.

(n-octanol/water)

**Auto-ignition temperature** > 700 °F (> 371.11 °C)

**Decomposition temperature** Not available.

**Viscosity** 500 cP Approx. (77 °F (25 °C))

Other information

VOC 0.2 lb/gal maximum

## 10. Stability and reactivity

Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.

Stable under normal temperature conditions. **Chemical stability** Possibility of hazardous Hazardous polymerization does not occur. reactions

**Conditions to avoid** Avoid temperatures exceeding the flash point. Contact with incompatible materials. Do not overheat

product.

**Incompatible materials** Strong oxidizing agents.

**Hazardous decomposition** Upon decomposition, this product may yield sulfur dioxide, carbon monoxide, carbon dioxide and/or products

low molecular weight hydrocarbons. Hydrogen sulfide.

# 11. Toxicological information

Information on likely routes of exposure

Inhalation Prolonged inhalation may be harmful. Skin contact May cause an allergic skin reaction.

Eye contact May be irritating to eyes.

**Ingestion** Expected to be a low ingestion hazard.

Material name: BLACKSNAKE-WP™

Symptoms related to the physical, chemical and toxicological characteristics Direct contact with eyes may cause temporary irritation.

Information on toxicological effects

**Acute toxicity** Not available.

Skin corrosion/irritation Prolonged skin contact may cause temporary irritation.

Serious eye damage/eye

irritation

May be irritating to eyes.

Respiratory or skin sensitization

Not available. Respiratory sensitization

Skin sensitization May cause allergic skin disorders in sensitive individuals.

Germ cell mutagenicity No data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity This product contains crystalline silica. Silica is a known carcinogen; however in this encapsulated

form the normal routes of exposure are unavailable.

IARC Monographs. Overall Evaluation of Carcinogenicity

ASPHALT (CAS 8052-42-4) 2B Possibly carcinogenic to humans.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)

Not regulated.

**US. National Toxicology Program (NTP) Report on Carcinogens** 

Not listed.

Not classified. Reproductive toxicity Specific target organ toxicity single exposure

Not classified.

Specific target organ toxicity

- repeated exposure

Not classified.

**Aspiration hazard** Not available.

**Chronic effects** Prolonged inhalation may be harmful.

**Further information** This product has no known adverse effect on human health.

### 12. Ecological information

**Ecotoxicity** Not expected to be harmful to aquatic organisms.

Product		Species	Test Results	
ERTECH™ 3036				
Aquatic				
Crustacea	EC50	Daphnia	43237.5 mg/l, 48 hours estimated	
Fish	LC50	Fish	27336.4766 mg/l, 96 hours estimated	

<sup>\*</sup> Estimates for product may be based on additional component data not shown.

Persistence and degradability No data is available on the degradability of this product.

**Bioaccumulative potential** No data available. Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

### 13. Disposal considerations

Material name: BLACKSNAKE-WP™

**Disposal instructions**Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose in

accordance with all applicable regulations. No components are identified as hazardous wastes.

Disposal recommendations are based on uncontaminated material.

Local disposal regulations

Dispose in accordance with all applicable regulations.

**Hazardous waste code**The waste code should be assigned in discussion between the user, the producer and the waste

disposal company. Not applicable.

Waste from residues / unused products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal

instructions). Avoid discharge into water courses or onto the ground.

**Contaminated packaging** Empty containers should be taken to an approved waste handling site for recycling or disposal.

Since emptied containers may retain product residue, follow label warnings even after container is

emptied.

# 14. Transport information

#### DOT

Not regulated as dangerous goods.

#### **IATA**

Not regulated as dangerous goods.

#### **IMDG**

Not regulated as dangerous goods.

Transport in bulk according to Not available.

Annex II of MARPOL 73/78

and the IBC Code

## 15. Regulatory information

**US federal regulations** All components are on the U.S. EPA TSCA Inventory List.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

**CERCLA Hazardous Substance List (40 CFR 302.4)** 

Not listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)

Not regulated.

### Superfund Amendments and Reauthorization Act of 1986 (SARA)

#### SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous chemical Yes

Classified hazard categories

Serious eye damage or eye irritation Respiratory or skin sensitization

SARA 313 (TRI reporting)

Not regulated.

# Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

**Safe Drinking Water Act** 

Not regulated.

(SDWA)

### **US state regulations**

### **California Proposition 65**



WARNING: WARNING: This product contains a chemical known to the State of California to cause cancer.

## California Proposition 65 - CRT: Listed date/Carcinogenic substance

ASPHALT (CAS 8052-42-4) Listed: January 1, 1990

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

ASPHALT (CAS 8052-42-4)

#### **International Inventories**

Country(s) or region	Inventory name	On inventory (yes/no)*	
Australia	Australian Inventory of Chemical Substances (AICS)	Yes	
Canada	Domestic Substances List (DSL)	Yes	
Canada	Non-Domestic Substances List (NDSL)	No	
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes	
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes	
Europe	European List of Notified Chemical Substances (ELINCS)	No	
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes	
Korea	Existing Chemicals List (ECL)	Yes	
New Zealand	New Zealand Inventory	Yes	
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes	
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	Yes	
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes	

<sup>\*</sup>A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

# 16. Other information, including date of preparation or last revision

**Issue date** 12-08-2021

Version # 01

**Further information** HMIS® is a registered trade and service mark of the NPCA.

NFPA ratings Health: 1

Flammability: 1 Instability: 0

References ACGIH

EPA: AQUIRE database

NLM: Hazardous Substances Data Base

US. IARC Monographs on Occupational Exposures to Chemical Agents

IARC Monographs. Overall Evaluation of Carcinogenicity National Toxicology Program (NTP) Report on Carcinogens

ACGIH Documentation of the Threshold Limit Values and Biological Exposure Indices

**Disclaimer** The information provided in this Safety Data Sheet is correct to the best of our knowledge,

information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. The information in the sheet was written

based on the best knowledge and experience currently available.

**Revision information** Composition / Information on Ingredients: Disclosure Overrides

Fire-fighting measures: Specific hazards arising from the chemical

Physical & Chemical Properties: Multiple Properties Regulatory information: US state regulations HazReg Data: International Inventories

GHS: Classification

Material name: BLACKSNAKE-WP™ SDS US

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).