

SAFETY DATA SHEET
JOINT-GUARD™ CJ PART A BASE

GARON

1. Product and Company Identification

Page 1 – 2/11/2021

Product Code: JOINT-GUARD™ CJ BASE
Product Name: JOINT-GUARD™ CJ BASE
Company Name: Garon Products Inc
2150 Rt 35, STE 250
Sea Girt, NJ 08750
Emergencies Involving Spills, Leaks
Fires, Exposures, or Accidents
Emergency Contact: CHEMTREC: (800) 424-9300

Phone Number:
800-631-5380

2. Hazards Identification

Skin Corrosion/Irritation, Category 2
Skin Sensitization, Category 1
Serious Eye Damage/Eye Irritation, Category 2A
Aquatic Toxicity (Chronic), Category 2
Acute Toxicity: (Acute), Category 2



GHS Signal Word:
GHS Hazard Phrases:

Danger:
H302 - Harmful if swallowed.
H315 – Causes skin irritation.
H317 - May cause an allergic skin reaction.
H319 - Causes serious eye irritation.
H411 - Toxic to aquatic life with long lasting effects.
GHS Precaution Phrases:
P261 - Avoid breathing dust/fume/gas/mist/vapors/spray.
P264 - Wash hands thoroughly after handling.
P270 - Do not eat, drink or smoke when using this product.
P272 - Contaminated work clothing should not be allowed out of the workplace.
P273 - Avoid release to the environment.
P280 - Wear protective gloves/protective clothing/eye protection/face protection.
GHS Response Phrases:
P301+330+331 - IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. Get medical aid.
P303+361+353 - IF ON SKIN (or hair): Remove/take off immediately all contaminated clothing. Rinse skin with water/shower.
P304+340 - IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical aid.
P305+351+338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P332+313 - If skin irritation occurs, get medical advice/attention.
P337+313 - If eye irritation persists, get medical advice/attention.
P370+378 – In case of fire, use water spray, dry chemical, carbon dioxide or alcohol-resistant foam.
P308+313 - IF exposed or concerned: Get medical attention/advice.
P403+235 – Store in cool/well-ventilated place. Store locked up.
P501 - Contact a licensed professional waste disposal service to dispose of this.

GHS Storage and Disposal Phrases:

Potential Health Effects

(Acute and Chronic):

Inhalation:

Skin Contact:

Eye Contact:

Ingestion:

Chronic inhalation may cause effects similar to those of acute inhalation.
May be harmful if inhaled.
Prolonged and/or repeated contact may cause irritation and/or dermatitis.
Causes eye irritation. Causes redness and pain.
May be harmful if swallowed.

3. Composition/Information on Ingredients

CAS #	Hazardous Components (Chemical Name)	Concentration
Proprietary	Epoxy Resin	50.0 - 65.0 %
14807-96-6	Talc	5.0 - 15.0 %
112945-52-5	Silica, amorphous treated	1.0 – 10%
13463-67-7	Titanium dioxide	1.0 – 10%

JOINT-GUARD™ CJ PART A BASE/PAGE 2

4. First Aid Measures

Emergency and First Aid Procedures:

In Case of Inhalation:

If inhaled, remove to fresh air. If breathing is difficult, give oxygen. Remove from exposure and move to fresh air immediately. Get medical aid.

In Case of Skin Contact:

Flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Wash clothing before reuse. If skin irritation occurs, get medical advice/attention.

In Case of Eye Contact:

Flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Get medical aid immediately.

In Case of Ingestion:

Never give anything by mouth to an unconscious person. Rinse mouth with water. Do NOT induce vomiting. Get medical aid.

Note to Physician:

Consult a physician. Show this safety data sheet to the doctor in attendance. Move out of dangerous area. Treat symptomatically and supportively.

5. Fire Fighting Measures

Suitable Extinguishing Media:

Use water spray, dry chemical, carbon dioxide, or appropriate foam. For large fires, apply water from as far as possible. Use very large quantities (flooding) of water applied as a mist or spray solid streams of water may be ineffective. Cool all affected containers with flooding quantities of water.

Fire Fighting Instructions:

Use water spray to cool unopened containers. Protective Equipment: Wear self-contained breathing apparatus and protective clothing to prevent contact with skin and eyes.

6. Accidental Release Measures

Steps To Be Taken in Case Material is Released or Stored:

Personal Precautions.

Use proper personal protective equipment.

Spills/Leaks: Control runoff and isolate discharged material for proper disposal. Use water spray to cool and disperse vapors and protect personnel.

7. Handling and Storage

Precautions To Be Taken in Handling:

Avoid contact with skin and eyes. Normal measures for preventive fire protection.

Precautions To Be Taken in Storing:

Containers which are opened must be carefully resealed and kept upright to prevent leakage. Suitable: Keep away from heat, sparks and open flame.

8. Exposure Control/Personal Protection

CAS #	Partial Chemical Name	OSHA TWA	ACGIH TWA
Proprietary	Epoxy Resin	N/A	N/A
14807-96-6	Talc	N/A	N/A
112945-52-5	Silica, amorphous treated	N/A	N/A
13463-67-7	Titanium dioxide	N/A	N/A

Respiratory Equipment (Specify Type):

For higher level protection use type OV/AG/P99 (US) or type ABEK-P2 (EU EN 143) respirator cartridges. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU). Where risk assessment shows air-purifying respirators are appropriate use a full-face respirator with multi-purpose combination (US) or type ABEK (EN 14387) respirator cartridges as a backup to engineering controls.

Eye Protection:

Safety glasses with side shield. For a higher degree of protection, wear chemical splash goggles.

Protective Gloves:

Wear appropriate protective gloves to prevent skin exposure, such as butyl rubber or nitrile rubber.

Other Protective Clothing:

Wear appropriate protective clothing to prevent skin exposure.

Engineering Controls (Ventilation etc.):

Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower. Use adequate general or local exhaust ventilation to keep airborne concentrations below the permissible exposure limits.

JOINT-GUARD™ CJ PART A BASE/PAGE 3

Work/Hygienic/Maintenance Practices:

Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end thoroughly after handling. Wash contaminated clothing before reuse.

9. Physical and Chemical Properties

Physical States:	<input type="checkbox"/> Gas	<input checked="" type="checkbox"/> Liquid	<input type="checkbox"/> Solid
Flash Point:	>200° F		
Boiling Point:	N/A		
Explosive Limits:	LEL: N/A	UEL: N/A	
Weight Per Gallon:	10.65 +/- .3		
Vapor Pressure (mm Hg):	N/A		
Vapor Density:	N/A		
Evaporation Rate:	N/A		
Percent Volatile:	0		

10. Stability and Reactivity

Stability:	Unstable <input type="checkbox"/>	Stable <input checked="" type="checkbox"/>
Conditions To Avoid – Instability:	Ignition Sources, Excess Heat	
Incompatibility - Materials To Avoid:	Strong oxidizing agents, acids, bases.	
Hazardous Decomposition Or Byproducts:	Nature of decomposition products unknown.	
Possibility of Hazardous Reactions:	Will occur <input type="checkbox"/>	Will not occur <input checked="" type="checkbox"/>
Conditions To Avoid – Hazardous Reactions:	No data available	

11. Toxicological Information

Toxicological Information: Irritation or Corrosion: Carcinogenicity/Other Information:

Causes serious eye irritation.
Carcinogenicity.
IARC: No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.
ACGIH: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.
NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.
OSHA: No component of this product present at levels greater than or equal to 0.1% is carcinogen or potential carcinogen by OSHA.

12. Ecological Information

General Ecological Information: Persistence and Degradability: Bioaccumulative Potential: Mobility in Soil:

Toxic to aquatic life with long lasting effects.
No data available.
No data available.
No data available.

13. Disposal Considerations

Waste Disposal Method:

Dispose of as unused product. This material may be burned in a chemical incinerator equipped with an after-burner and scrubber. Observe all federal, state and local environmental regulations. Contact a licensed professional waste disposal service to dispose of this material.

JOINT-GUARD™ CJ PART A BASE/PAGE 4

14. Transport Information

LANDS TRANSPORT (US DOT) Limited Quantity – Used for 1 gallon containers when shipped in the United States of America.
DOT Proper Shipping Name: 5 gal. pails – UN3082, PG III, Class 9 Environmentally hazardous substance, liquid, n.o.s. (epoxy resin)



Marine Transport The marine pollutant mark is not required when transported in sizes of ≤5 L or ≤5 kg (per container).
IMDG Shipping: UN 3082, PG III, Class 9 Environmentally hazardous substance, liquid, n.o.s. (epoxy resin)



AIR TRANSPORT (ICAO/IATA)
ICAO/IATA SHIPPING NAME: UN 3082, PG III, Class 9 Environmentally hazardous substance, liquid, n.o.s. (epoxy resin)



15. Regulatory Information

EPA SARA (Superfund Amendments and Reauthorization Act of 1986) Lists

CAS #	Hazardous Components (Chemical Name)	S. 302 (EHS)	S. 302 (EHS)	S. 313 (TRI)
Proprietary	Epoxy Resin	No	No	No
14807-96-6	Talc	No	No	No
112945-52-5	Silica, amorphous treated	No	No	No
13463-67-7	Titanium dioxide	No	No	No

All components in this product are listed in the TSCA Inventory List.

V.O.C.: 0 LBS/GL (0 GMS/L)

16. Other Information

Revision Date: 2/11/2021

Additional Information About This Product:

Hazardous Material Information System III (U.S.A)

Health: 2
Flammability: 1
Reactivity: 0
Personal Protection: *

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings are not required on MSDSs under 29 CFR 1910. 1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA). HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by Garon Products Inc. and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.