

1. Product and Company Information

PRODUCT NAME: STEELZ™ PRO CR PART A
PRODUCT CODE: 29260
COMPANY NAME: Garon Products Inc
ADDRESS: PO Box 1924
CITY, STATE, ZIP: Wall, NJ 07719

INFORMATION PHONE: 732-223-2500
EMERGENCY PHONE: CHEMTREC: (800) 424-9300

DATE REVISED: 3/24/2024

2. Hazards Identification

Target Organ Systemic Toxicity (repeated exposure), Category 2
Skin Corrosion/Irritation, Category 2
Skin Sensitization, Category 1
Serious Eye Damage/Eye Irritation, Category 2A
Aquatic Toxicity (Chronic), Category 2
Skin Corrosion/Irritation, Category 3
Flammable Liquids, Category 3
Acute Toxicity: Oral, Category 4
Acute Toxicity: Inhalation, Category 4



GHS Signal Word:

Danger

GHS Hazard Phrases:

H226 – Flammable liquid and vapor.
H302 – Harmful if swallowed.
H315 – Causes skin irritation.
H317 – May cause an allergic skin reaction.
H319 – Causes serious eye irritation.
H373 – May cause damage to organs through prolonged or repeated exposure.

GHS Precaution Phrases:

H411 – Toxic to aquatic life with long lasting effects.
P210 – Keep away from heat/sparks/open flames/hot surfaces. – No smoking.
P233 – Keep container tightly closed.
P241 – Use explosion-proof electrical/ventilating/lighting equipment.
P242 – Use only non-sparking tools.
P260 – Do not breathe dust/fume/gas/mist/vapors/spray.
P264 – Wash hands thoroughly after handling.
P270 – Do not eat, drink or smoke when using this product.

GHS Response Phrases:

P280 – Wear protective gloves/protective clothing/eye protection/face protection.
P301+330+331 – IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. Get medical aid.
P303+361+353 - IF ON SKIN (or hair): Remove/take off immediately all contaminated clothing. Rinse skin with water/shower.
P304+340 - IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical attention.
P305+351+338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P332+313 – If skin irritation occurs, get medical advice/attention.
P337+313 - If eye irritation persists, get medical advice/attention.
P370+378 - In case of fire, use water spray, dry chemical, carbon dioxide, or alcohol-resistant foam.
P403+235 - Store in cool/well-ventilated place. Store locked up.
P501 - Contact a licensed professional waste disposal service to dispose of this material.

GHS Storage and Disposal Phrases:

Potential Health Effects (Acute and Chronic):

Inhalation:

Chronic inhalation may cause effects similar to those of acute inhalation.

Skin Contact:

May be harmful if inhaled. Causes respiratory tract irritation. Vapors may cause dizziness or suffocation. May be harmful if absorbed through the skin. Causes skin irritation.

Eye Contact: Causes eye irritation.
Ingestion: May be harmful if swallowed. Ingestion of large amounts may cause gastrointestinal irritation.

3. Composition/Information on Ingredients

<u>CAS #</u>	<u>Hazardous Components (Chemical Name)</u>	<u>Concentration</u>
14808-60-7	Silicon Dioxide	50.0 – 55.0%
25068-38-6	Epoxy resin	25.0 – 35.0%
13463-67-7	Titanium dioxide	5.0 - 15.0%
64742-95-6	Aromatic Solvent	1.0 – 5.0%
84852-15-3	Phenol, 4-nonyl-, branched	1.0 – 5.0%
110-43-0	2-Heptanone	1.0 – 5.0%

4. First Aid Measures

Emergency and First Aid Procedures:

In Case of Inhalation: If breathed in, remove to fresh air. If breathing is difficult, give oxygen. Remove from exposure and move to fresh air immediately. Get medical aid.

In Case of Skin Contact: Flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Wash clothing before reuse. If skin irritation occurs, get medical advice/attention.

In Case of Eye Contact: Flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Get medical aid immediately.

In Case of Ingestion: Never give anything by mouth to an unconscious person. Rinse mouth with water. Do NOT induce vomiting. Get medical aid.

Note to Physician: Consult a physician. Show this safety data sheet to the doctor in attendance. Move out of dangerous area. Treat symptomatically and supportively.

5. Fire Fighting Measures

Suitable Extinguishing Media: Use water spray, dry chemical, carbon dioxide, or alcohol-resistant foam. For large fires, apply water from as far as possible. Use very large quantities (flooding) of water applied as a mist or spray; solid streams of water may be ineffective. Cool all affected containers with flooding quantities of water.

Fire Fighting Instructions:

Flammable Properties and Hazards:

Use water spray to cool unopened containers. Protective Equipment: Wear self-contained breathing apparatus and protective clothing to prevent contact with skin and eyes. Specific Hazard(s): Flammable Liquid. Emits toxic fumes under fire conditions. During a fire, irritating and highly toxic gases may be generated by thermal decomposition or combustion. Use water spray to keep fire-exposed containers cool. Flammable liquid and vapor. Vapors are heavier than air and may travel to a source of ignition and flash back. Vapors can spread along the ground and collect in low or confined areas. Vapor may travel considerable distance to source of ignition and flash back. Container explosion may occur under fire conditions. Forms explosive mixtures in air.

6. Accidental Release Measures

Steps To Be Taken In Case Material Is Released Or Spilled: Personal precautions. Use personal protective equipment. Spills/Leaks: Control runoff and isolate discharged material for proper disposal. Use water spray to cool and disperse vapors and protect personnel.

7. Handling and Storage

Precautions To Be Taken in Handling: Avoid contact with skin and eyes. Normal measures for preventive fire protection. Avoid inhalation of vapor or mist. Keep away from sources of ignition - No smoking. Take measures to prevent the buildup of electrostatic charge.

**Precautions To Be Taken
in Storing:**

Containers which are opened must be carefully resealed and kept upright to prevent leakage. Keep away from heat, sparks, and open flame.

8. Exposure Controls/Personal Protection

CAS #	Partial Chemical Name	OSHA TWA	ACGIH TWA
14808-60-7	Silicon Dioxide	PEL: 8825 ppm/(%SiO2+5)	TLV: 0.05 MG/M3 (R)
25068-38-6	Epoxy resin	N/E	N/E
13463-67-7	Titanium dioxide	PEL: 15 (dust) mg/m3 TLV: 10 mg/m3	
64742-95-6	Aromatic Solvent	PEL: 100 ppm	TLV: 100 ppm STEL: 150 PPM
84852-15-3	Phenol, 4-nonyl-, branched	N/A	N/A
110-43-0	2-Heptanone	PEL: 100 ppm	TLV: 50 ppm

**Respiratory Equipment
(Specify Type):**

For higher level protection use type OV/AG/P99 (US) or type ABEK-P2 (EU EN 143) respirator cartridges. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU). Where risk assessment shows air-purifying respirators are appropriate use a full-face respirator with multi-purpose combination (US) or type ABEK (EN 14387) respirator cartridges as a backup to engineering controls.

Eye Protection:

Safety glasses with side shield. For a higher degree of protection, wear chemical splash goggles.

Protective Gloves:

Wear appropriate protective gloves to prevent skin exposure, such as butyl rubber or nitrile rubber.

Other Protective Clothing:

Wear appropriate protective clothing to prevent skin exposure.

**Engineering Controls
(Ventilation etc.):**

Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower. Use adequate general or local exhaust ventilation to keep airborne concentrations below the permissible exposure limits.

**Work/Hygienic/Maintenance
Practices:**

Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.

9. Physical and Chemical Properties

Physical States:	<input type="checkbox"/> Gas	<input checked="" type="checkbox"/> Liquid	<input type="checkbox"/> Solid
Flash Point:	102°F		
Boiling Point:	250°F		
Explosive Limits:	LEL: 1.0	UEL: 7.0	
Weight Per Gallon:	14.7 ± .5		
Vapor Pressure (mm Hg):	3 @ 68°F		
Vapor Density:	Heavier than Air		
Evaporation Rate:	Slower than Ether		
Percent Volatile:	8 (vol)		

10. Stability and Reactivity

Stability:	Unstable <input type="checkbox"/>	Stable <input checked="" type="checkbox"/>
Conditions To Avoid – Instability:	Heat, flames and sparks	
Incompatibility - Materials To Avoid:	Bases, strong oxidizing agents	
Hazardous Decomposition or Byproducts:	Nature of decomposition products unknown.	
Possibility of Hazardous Reactions:	Will occur <input type="checkbox"/>	Will not occur <input checked="" type="checkbox"/>
Conditions To Avoid – Hazardous Reactions:	No data available.	

11. Toxicological Information

Toxicological Information: Respiratory or skin sensitization: Germ cell mutagenicity. Reproductive toxicity - no data available.
Irritation or Corrosion: Aspiration hazard. Epidemiology: No information found.
Teratogenicity: No information available. Reproductive Effects: Mutagenicity: No data available.
Carcinogenicity/Other Information: These products contain more than 0.1% crystalline silica (CAS #14808-60-7) which has been classified by IARC a Class 1 carcinogen. Normal application procedures pose no hazard since the silica is set and encapsulated, but grinding or sanding dried films may yield respirable silica dusts. Control exposures to less than 0.1 mg per cubic meter of air using approved dust filter respirators. Skin contact: Prolonged or repeated contact with product may cause slight skin irritation. Impervious gloves should be worn if prolonged skin contact is likely.

ACGIH Carcinogens

Quartz (CAS 14808-60-7) A2 Suspected human carcinogen

IARC Monographs, Overall Evaluation of Carcinogenicity

Quartz (CAS 14808-60-7) 1 Carcinogenic to humans

US NTP Report on Carcinogens: Known carcinogen

Quartz (CAS 14808-60-7) Known to be human carcinogen

OSHA PEL: Exposure to airborne crystalline silica shall not exceed an 8 hour time weighted average limit as stated in 29CFR 1910.1000, Table-Z-1-A Air contaminants, specifically: Silica, Crystalline Quartz (Respirable) 0.1 MG/M3. ACGIH TLV-TWA: 01 MG/M3. NIOSH Maximum permissible conc. 0.05 MG/M3, 10 hour workday, 40 hour week. ⚠ The following product contains substances known to the State of California to cause cancer, birth defects, or other reproductive hazards: Benzene, Toluene, Crystalline Silica.

12. Ecological Information

General Ecological Information: No Data Available
Persistence and Degradability: No Data Available
Bioaccumulative Potential: No Data Available
Mobility in Soil: No Data Available

13. Disposable Considerations

Waste Disposal Method: Dispose of as unused product. This material may be burned in a chemical incinerator equipped with an afterburner and scrubber. Observe all federal, state, and local environmental regulations. Contact a licensed professional waste disposal service to dispose of this material.

14. Transport Information

Land Transport (US DOT): Limited Quantity - Used for 1 gallon containers when shipped in the United States of America.
DOT Proper Shipping Name: UN1263, Paint Related Material, 3, PG III – 5 gallon pails



Marine Transport IMDG Shipping: UN1263, Paint Related Material, 3, PG III



Air Transport (ICAO/IATA): UN1263, Paint Related Material, 3, PG III
IATA Shipping Name:



15. Regulatory Information



EPA SARA (Superfund Amendments and Reauthorization Act of 1986) Lists

CAS #	Hazardous Components (Chemical Name)	S. 302 (EHS)	S. 304 RQ	S. 313 (TRI)
14808-60-7	Silicon Dioxide	No	No	No
25068-38-6	Epoxy resin	No	No	No
13463-67-7	Titanium dioxide	No	No	No
64742-95-6	Aromatic Solvent	No	No	No
84852-15-3	Phenol, 4-nonyl-, branched	No	No	No
110-43-0	2-Heptanone	No	No	No

All components in this product are listed in the TSCA Inventory List.

V.O.C. (mixed) .60 lbs/gal (72 GMS/L)

16. Other Information

Revision Date: 3/24/2023

Additional Information About This Product:

Hazardous Material Information System III (U.S.A)

Health: 2
Flammability: 2
Reactivity: 0
Personal Protection: *

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings are not required on MSDSs under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA). HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by Garon Products Inc. and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.

1. Product and Company Identification

PRODUCT NAME: STEELZ™ PRO CR PART B
PRODUCT CODE: 29260

COMPANY NAME: Garon Products Inc.
ADDRESS: PO Box 1924
CITY, STATE, ZIP: Wall, NJ 07719

INFORMATION PHONE: 732-223-2500
EMERGENCY PHONE: CHEMTREC: (800)424-9300

DATE REVISED: 3/24/2024

2. Hazards Identification

Skin Corrosion/Irritation, Category 1B
Serious Eye Damage/Eye Irritation, Category 1
Acute Toxicity: Oral, Category 4
Skin Sensitization, Category 1



GHS Signal Word

Danger

GHS Hazard Phrases:

H302 – Harmful if swallowed.

H314 - Causes severe skin burns and eye damage.

H361 – Suspected of damaging fertility or the unborn child.

GHS Precaution Phrases:

P202 – Do not handle until all safety precautions have been read and understood.

P260 - Do not breathe dust/fume/gas/mist/vapors/spray.

P264 - Wash hands thoroughly after handling.

P270 – Do not eat, drink or smoke when using this product.

P280 - Wear protective gloves/protective clothing/eye protection/face protection.

P281 – Use personal protective equipment as required.

GHS Response Phrases:

P301+330+331 – IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. Get medical aid.

P303+361+353 - IF ON SKIN (or hair): Remove/take off immediately all contaminated clothing. Rinse skin with water/shower.

P304+340 - IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical attention.

P305+351+338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P312 - Call a POISON CENTER/doctor if you feel unwell.

P332+313 – If skin irritation occurs, get medical advice/attention.

P337+313 - If eye irritation persists, get medical advice/attention.

P370+378 - In case of fire, use water spray, dry chemical, carbon dioxide, or alcohol-resistant foam.

P403+235 - Store in cool/well-ventilated place. Store locked up.

P501 - Contact a licensed professional waste disposal service to dispose of this material.

GHS Storage and Disposal Phrases:

Potential Health Effects

(Acute and Chronic):

Inhalation:

Chronic inhalation may cause effects similar to those of acute inhalation.

May be harmful if inhaled. Material is extremely destructive to the tissue of the mucous membranes and upper respiratory tract. Material may be irritating to mucous membranes and upper respiratory tract.

Skin Contact:

May be harmful if absorbed through the skin. Causes skin burns. Causes severe skin irritation.

Eye Contact:

Causes eye burns. Causes severe eye irritation.

Ingestion:

Harmful if swallowed.

3. Composition/Information on Ingredients

CAS #	Hazardous Components (Chemical Name)	Concentration
Proprietary	Epoxy Amine Resin	90.0 - 95.0 %
100-51-6	Benzyl Alcohol	5.0 - 10.0 %

4. First Aid Measures

Emergency and First Aid Procedures:

In Case of Inhalation:	If inhaled, remove to fresh air. If breathing is difficult, give oxygen. Remove from exposure and move to fresh air immediately. Get medical aid.
In Case of Skin Contact:	Flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Wash clothing before reuse. If skin irritation occurs, get medical advice/attention.
In Case of Eye Contact:	Flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Get medical aid immediately.
In Case of Ingestion:	Never give anything by mouth to an unconscious person. Rinse mouth with water. Do NOT induce vomiting. Get medical aid.
Note to Physician:	Consult a physician. Show this safety data sheet to the doctor in attendance. Move out of dangerous area. Treat symptomatically and supportively.

5. Fire Fighting Measures

Suitable Extinguishing Media:	Use water spray, dry chemical, carbon dioxide, or alcohol-resistant foam. For large fires, apply water from as far as possible. Use very large quantities (flooding) of water applied as a mist or spray; solid streams of water may be ineffective. Cool all affected containers with flooding quantities of water.
Fire Fighting Instructions: apparatus	Use water spray to cool unopened containers. Protective Equipment: Wear self-contained breathing apparatus and protective clothing to prevent contact with skin and eyes. Specific Hazard(s): Flammable Liquid. Emits toxic fumes under fire conditions. During a fire, irritating and highly toxic gases may be generated by thermal decomposition or combustion. Use water spray to keep fire-exposed containers cool. Flammable liquid vapor. Vapors are heavier than air and may travel to a source of ignition and flash back. Vapors can spread along the ground and collect in low or confined areas.
Flammable Properties and Hazards:	Vapor may travel considerable distance to source of ignition and flash back. Container explosion may occur under fire conditions. Forms explosive mixtures in air.

6. Accidental Release Measures

Steps To Be Taken In Case Material is Released or Spilled:	Personal precautions. Use personal protective equipment. Spills/Leaks: Control runoff and isolate discharged material for proper disposal. Use water spray to cool and disperse vapors and protect personnel.
---	---

7. Handling and Storage

Precautions To Be Taken in Handling:	Avoid contact with skin and eyes. Normal measures for preventive fire protection. Avoid inhalation of vapor or mist.
Precautions to be Taken in Storing	Keep away from sources of ignition - No smoking. Take measures to prevent the build-up of electrostatic charge. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Keep away from heat, sparks, and open flame.

8. Exposure Controls/Personal Protection

CAS #	Partial Chemical Name	OSHA TWA	ACGIH TWA
-------	-----------------------	----------	-----------

Proprietary
100-51-6

Epoxy Amine Resin
Benzyl Alcohol

N/E
N/E

N/E
N/E

**Respiratory Equipment
(Specify Type):**

For higher level protection use type OV/AG/P99 (US) or type ABEK-P2 (EU EN 143) respirator cartridges. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU). Where risk assessment shows air-purifying respirators are appropriate use a full-face respirator with multi-purpose combination (US) or type ABEK (EN 14387) respirator cartridges as a backup to engineering controls.

Eye Protection:

Safety glasses with side shield. For a higher degree of protection, wear chemical splash goggles.

Protective Gloves:

Wear appropriate protective gloves to prevent skin exposure, such as butyl rubber or nitrile rubber.

Other Protective Clothing:

Wear appropriate protective clothing to prevent skin exposure.

**Engineering Controls
(Ventilation, etc.):**

**Work/Hygienic/Maintenance
Practices:**

Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower. Use adequate general or local exhaust ventilation to keep airborne concentrations below the permissible exposure limits. Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday. Wash thoroughly after handling. Wash contaminated clothing before reuse.

9. Physical and Chemical Properties

Physical States:	<input type="checkbox"/> Gas	<input checked="" type="checkbox"/> Liquid	<input type="checkbox"/> Solid
Flash Point:	230°F		
Boiling Point:	250°F		
Explosive Limits:	LEL: N/A	UEL: N/A	
Weight Per Gallon:	8.35 +/- .3		
Vapor Pressure (mm Hg):	N/A		
Vapor Density:	N/A		
Evaporation Rate:	N/A		
Percent Volatile:	0 (VOL.)		

10. Stability and Reactivity

Stability:	Unstable <input type="checkbox"/>	Stable <input checked="" type="checkbox"/>
Conditions to Avoid – Instability:	Excessive heat, flames and sparks	
Incompability – Materials to Avoid:	Bases, Strong oxidizing agents	
Hazardous Decomposition or Byproducts:	Nature of decomposition products unknown	
Possibility of Hazardous Reactions:	No data available	

11. Toxicological Information

Toxicological Information: Irritation or Corrosion:	Skin - rabbit - Corrosive. Serious eye damage/eye irritation: Eyes - rabbit - Severe eye irritation.	
Carcinogenicity/Other Information:	IARC: No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC. ACGIH: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH. NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP. OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.	

12. Ecological Information

Persistence and Degradability:	No data available
Bioaccumulative Potential:	No data available
Mobility in Soil:	No data available

13. Disposal Considerations

Waste Disposal Method:

Dispose of as unused product. This material may be burned in a chemical incinerator equipped with an afterburner and scrubber. Observe all federal, state, and local environmental regulations. Contact a licensed professional waste disposal service to dispose of this material.

14. Transport Information

LANDS TRANSPORT (US DOT)

DOT Proper Shipping Name:

Limited Quantity - Used for 1 gallon and quart containers when shipped in the United States of America
UN3066, Paint Related Material, 8, PG III (sizes larger than 1 gallon)

IMDG Shipping:

UN3066, Paint Related Material, 8, PG III



AIR TRANSPORT (ICAO/IATA)

ICAO/IATA SHIPPING NAME:

UN3066, Paint Related Material, 8, PG III



15. Regulatory Information

EPA SARA (Superfund Amendments and Reauthorization Act of 1986) Lists

CAS #	Hazardous Components (Chemical Name)	S. 302 (EHS)	S. 304 RQ	S. 313 (TRI)
Proprietary	Epoxy Amine Resin	No	No	No
100-51-6	Benzyl Alcohol	No	No	No

All components in this product are listed in the TSCA Inventory List.

V.O.C. (mixed) .60 lbs/gal (72 GMS/L)

16. Other Information

Revision Date: 10/30/2023

Additional Information About This Product:

Hazardous Material Information System III (U.S.A)

Health: 3

Flammability: 1

Reactivity: 0

Personal Protection: *

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings are not required on MSDSs under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA). HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by Garon Products Inc. and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.